

- DIE-CAST ALUMINIUM LAMP BODY
- HIGH EFFICIENCY SMD LED CHIPS
- IP44 WEATHERPROOF
- IC ABUTTED & COVERED
- COMPATIBLE WITH C-BUS
UNIVERSAL, LEADING AND TRAILING EDGE DIMMERS
- PRE-WIRED WITH FLEX & PLUG



EMC LM-79 LM-80 TM-21 ISTMT VEET IPART

Model Number	GL-AU09-DL10W	GL-AU09-DL20W-6	GL-AU09-DL30W-8
LED Chips	SMD 2835	SMD 2835	SMD 2835
Power	10W	20W	30W
Input Voltage	175-265VAC 50/60Hz	175-265VAC 50/60Hz	175-265VAC 50/60Hz
Lumens	750lm±5%	1800lm±5%	2700lm±5%
Power Factor	>0.9	>0.9	>0.9
CRI	>82	>82	>82
Color Temperature	3000K~6000K	3000K~6000K	3000K~6000K
Beam Angle	90°	90°	90°
Dimensions	Φ108*32mm	Φ190*50mm	Φ225*50mm
Cut Out	Φ90mm	Φ160mm	Φ190mm
IP Rating	IP44	IP44	IP44
IC Rating	IC-F	IC-F	IC-F
Operating Temperature	-25°C ~ +45°C	-25°C ~ +45°C	-25°C ~ +45°C
Life Time	50,000 Hours	50,000 Hours	50,000 Hours
Warranty	5 Years	5 Years	5 Years