

- HIGH LUMEN OUTPUT 130LM/W
- EASY AND FAST INSTALLATION
- SEALED LED MODULE INSECT PROOF
- BACK AND SIDE CABLE ENTRY POINTS
- LARGE TERMINAL BLOCK INSTALLED



EMC LM-79 LM-80 TM-21 ISTMT

Model Number	GL-AU01-BAT20W2F	GL-AU01-BAT36W4F	GL-AU01-BAT55W5F
LED Chips	SMD 2835	SMD 2835	SMD 2835
Power	20W	36W	55W
Input Voltage	220-240VAC 50/60Hz	220-240VAC 50/60Hz	220-240VAC 50/60Hz
Lumens	2600lm±5%	4680lm±5%	7150lm±5%
Power Factor	>0.9	>0.9	>0.9
CRI	>80	>80	>80
Color Temperature	3000K~6000K	3000K~6000K	3000K~6000K
Beam Angle	120°	120°	120°
Dimensions Weight	600*80*65mm 1.15Kg	1200*80*65mm 2.04Kg	1500*80*65mm 2.6Kg
Cut Out	N/A	N/A	N/A
IP Rating	IP44	IP44	IP44
Operating Temperature	-25°C ~ +45°C	-25°C ~ +45°C	-25°C ~ +45°C
Life Time	50,000 Hours	50,000 Hours	50,000 Hours
Warranty	5 Years	5 Years	5 Years

Additional Function: Dimmable, Microwave Sensor, Emergency Lighting.